

PUFAS Cleaning and Degreasing Powder SC super-clean

PUFAS Anlauger und Entfetter SC super-clean

- ideal substrate pretreatment for all types of coating to existing paintwork
- powerfully removes grease, dirt, nicotine etc.
- creates substrates with good key for reliable adhesion
- quickly soluble
- high-performance
- odourless

Instructions for use:

PUFAS Cleaning and Degreasing Powder SC super-clean is the ideal surface pre-treatment for painted surfaces before applying subsequent coats of paints. Ideally suited for cleaning inaccessible areas, which cannot be sanded down (e.g. radiators). Removes grease, oil and other difficult to remove soiling from the surface, whereby an adhesive, clean surface results. Not suitable for cleaning metals (zinc, aluminium, etc.)

Technical specifications:

Components: sodium carbonate, tri-sodium phosphate
pH-value: approx. 11

Application:

Stir 100 g PUFAS Cleaning and Degreasing Powder SC super-clean into 1 l water and completely dissolve. Apply the solution using a sponge or brush and leave to act for approx. 10 minutes. A higher concentration can be used for severe soiling (100 g to 0.75 l). Then rinse off the treated surface well with water and leave to dry before continuing applying any further treatment.

Note:

Please see EU safety data sheet for all safety-related data (EU-CLP)

Clean any working equipment with water after use.

Considerations disposal:

Please see EU safety data sheet section 13 (EWC).

Storage:

Keep cool but protected from frost! Keep container well closed!

Available sizes:

100 g	4007954050019	005001000	REG
500 g	4007954050064	005012000	REG
5 kg	4007954050033	005003000	REG

Note:

All details and data presented in this information sheet are based on our practical experience and laboratory investigations, and reflect the current state of the art. They can, however, only serve as general guidance and shall provide no guarantee of specific properties or performance. Given that the conditions for storage, transportation and application of products are beyond our control, no legal liability may be construed from the information presented here. It shall be the responsibility of the user to check the product's suitability for the envisaged purpose under the specific site or project conditions.