



# Sanderson

## ACTIVE EMULSION

### DESCRIPTION

Active Emulsion offers ultimate durability. For use on interior walls, metal and woodwork, it's tougher than traditional Emulsions, making it easier to clean and the ideal solution for high traffic areas. A fast drying, low odour, low sheen finish ideal for use where durability and performance is important.

### KEY PROPERTIES

- Ultimate durability and performance.
- Washable and stain resistant
- Ideal for high wear/traffic areas such as hallways, kitchens and children's bedrooms.
- Low sheen finish

### PREPARATION

All surfaces should be sound, clean, dry and free from grease. Remove any loose or flaking paint. Rub down sound glossy surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of a Water/Acrylic Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. Seal absorbent surfaces with a solution of up to 1 part water to 4 parts Active Emulsion. Prime bare timber and metal surfaces with an appropriate primer. Allow radiators to cool before painting.

### APPLICATION

Stir well before use and apply by brush, roller or paint pad. When using a roller, use a medium pile synthetic type. Do not overfill the tray. Ensure roller is loaded evenly. If using a brush, load generously. Apply liberally and evenly; avoid overspreading.

### CLEANING

Remove as much product as possible from equipment before cleaning. Clean immediately after use in warm soapy water and rinse thoroughly. Replace lid firmly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty wastes paint into drains or watercourses.

### PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one and octhilineone (ISO). May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children

- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell. Safety data sheet available on request.

### RECOMMENDED USES

Suitable for interior use

### TYPE OF SUBSTRATE

Interior walls and ceilings. Suitably primed woodwork, metal and radiators.

### COLOUR RANGE

154 colours.

### FINISH

Low sheen

### VOLUME SOLID

35%

### COVERAGE

Approximately 12 square metres per litre depending on the nature and porosity of the surface.

### DRYING TIME

Touch dry in 1 - 2 hours. Recoatable after 2 - 4 hours.

### TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

### CLEANER

Clean water

### VOC CONTENT

- Low VOC Content 0.3 - 7.99%
- VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.
- EU limit value for this product (Cat A/a): 30g/l (2010).
- This product contains max 15g/l VOC.

### FILM THICKNESS

Wet: 83µm, Dry: 29µm.

### SIZES

2.5 Litre, 5 Litre