



ZOFFANY

ACRYLIC EGGSHELL

DESCRIPTION

Water Based Eggshell is a premium quality, water-based, low sheen finish formulated for interior use on walls, ceilings, wood and metal work. It provides a low odour, quick drying finish that is resistant to condensation and yellowing, making it ideal for use in kitchens, bathrooms, hallways and conservatories. Suitable for exterior use on woodwork such as doors and window frames.

KEY PROPERTIES

- A quick drying, low odour, low sheen finish for interior use.
- Produces a smooth, washable surface that resists condensation.
- Tough, durable and non-yellowing.
- High opacity and hardwearing.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime bare surfaces with the appropriate Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of Water/Acrylic Based Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

APPLICATION

Stir well. Easy to apply by brush or roller. Seal absorbent surfaces with a coat of Acrylic Eggshell thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C.

CLEANING

Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one (EC no.247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no.220-239-6) (3:1), octhiline (ISO) and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.

- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

RECOMMENDED USES

Suitable for interior/Exterior use.

TYPE OF SUBSTRATE

Wood, metal and plaster. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations.

COLOUR RANGE

Alchemy of Colour collection, 156 Colours

FINISH

Low Sheen

VOLUME SOLID

36%

COVERAGE

Approximately 12 square metres per litre depending on the nature and porosity of the surface

DRYING TIME

Touch dry in 1 - 2 hours. Recoatable after 2 - 4 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Store away from heat and flame.

CLEANER

Clean water

VOC CONTENT

- Low VOC Content 0.3-7.99%
- VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.
- EU limit value for this product (Cat A/a): 30g/l (2010).
- This product contains max 10g/l VOC.

FILM THICKNESS

Wet: 83µm, Dry: 30µm.

SIZES

1 Litre, 2.5 Litre